



OFFICIAL LISTING

NSF Certifies that the products appearing on this Listing conform to the requirements of
NSF/ANSI/CAN 61 - Drinking Water System Components - Health Effects

This is the Official Listing recorded on January 13, 2025.

Alloy Piping Products, LLC
2330 Holmes Road
Houston, TX 77051
713-799-9235

Facility: Houston, TX

Pipes and Related Products

Trade Name	Size	Water Contact Temp	Water Contact Material	
Fittings [G]				
180° -Seamless	1/2 - 24 in	C. HOT	SS	A
45° Long Radius Elbow-Seamless	1/2 - 24 in	C. HOT	SS	A
45° Long Radius Elbow-Welded	1/2 - 24 in	C. HOT	SS	A
90° Long Radius Elbow-Seamless	1/2 - 24 in	C. HOT	SS	A
90° Long Radius Elbow-Welded	1/2 - 24 in	C. HOT	SS	A
90° Short Radius Elbow-Seamless	1/2 - 24 in	C. HOT	SS	A
90° Short Radius Elbow-Welded	1/2 - 24 in	C. HOT	SS	A
Blind Flange	1/2 - 12 in	C. HOT	SS	A
Cap-Seamless	1/2 - 24 in	C. HOT	SS	A
Cap-Welded	1/2 - 24 in	C. HOT	SS	A
Concentric Reducer-Seamless	1/2 - 24 in	C. HOT	SS	A
Concentric Reducer-Welded	1/2 - 24 in	C. HOT	SS	A
Cross-Welded	1/2 - 24 in	C. HOT	SS	A
Eccentric Reducer-Seamless	1/2 - 24 in	C. HOT	SS	A
Eccentric Reducer-Welded	1/2 - 24 in	C. HOT	SS	A
Equal Tee-Seamless	1/2 - 24 in	C. HOT	SS	A
Equal Tee-Welded	1/2 - 24 in	C. HOT	SS	A
Hex Head Thread Plug	1/2-4 in	C. HOT	SS	A

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



Reducer Tee-Seamless	1/2 - 24 in	C. HOT	SS	A
Reducer Tee-Welded	1/2 - 24 in	C. HOT	SS	A
Round Head Thread Plug	1/2-4 in	C. HOT	SS	A
Slip on Flange	1/2 - 12 in	C. HOT	SS	A
Socket Olet	1/2-4 in	C. HOT	SS	A
Socket Weld 45	1/2-4 in	C. HOT	SS	A
Socket Weld 90	1/2-4 in	C. HOT	SS	A
Socket Weld Cap	1/2-4 in	C. HOT	SS	A
Socket Weld Coupling	1/2-4 in	C. HOT	SS	A
Socket Weld Cross	1/2-4 in	C. HOT	SS	A
Socket Weld Flange	1/2 - 12 in	C. HOT	SS	A
Socket Weld Half Coupling	1/2-4 in	C. HOT	SS	A
Socket Weld Tee	1/2-4 in	C. HOT	SS	A
Socket Weld Union	1/2-4 in	C. HOT	SS	A
Stub End-Seamless	1/2 - 24 in	C. HOT	SS	A
Stub End-Welded	1/2 - 24 in	C. HOT	SS	A
Threaded 90	1/2-4 in	C. HOT	SS	A
Threaded Cap	1/2-4 in	C. HOT	SS	A
Threaded Coupling	1/2-4 in	C. HOT	SS	A
Threaded Cross	1/2-4 in	C. HOT	SS	A
Threaded Flange	1/2 - 12 in	C. HOT	SS	A
Threaded Half Coupling	1/2-4 in	C. HOT	SS	A
Threaded Olet	1/2-4 in	C. HOT	SS	A
Threaded Street 90	1/2-4 in	C. HOT	SS	A
Threaded Tee	1/2-4 in	C. HOT	SS	A
Threaded Union	1/2-4 in	C. HOT	SS	A
Threaded Weld 45	1/2-4 in	C. HOT	SS	A
Welded Olet	1/2-24 in	C. HOT	SS	A
Weldneck Flange	1/2 - 12 in	C. HOT	SS	A

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Facility: Shreveport, LA

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



Pipes and Related Products

Trade Name	Size	Water Contact Temp	Water Contact Material	
Fittings [G]				
180° -Seamless	1/2 - 24 in	C. HOT	SS	A
45° Long Radius Elbow-Seamless	1/2 - 24 in	C. HOT	SS	A
45° Long Radius Elbow-Welded	1/2 - 24 in	C. HOT	SS	A
90° Long Radius Elbow-Seamless	1/2 - 24 in	C. HOT	SS	A
90° Long Radius Elbow-Welded	1/2 - 24 in	C. HOT	SS	A
90° Short Radius Elbow-Seamless	1/2 - 24 in	C. HOT	SS	A
90° Short Radius Elbow-Welded	1/2 - 24 in	C. HOT	SS	A
Blind Flange	1/2 - 12 in	C. HOT	SS	A
Cap-Seamless	1/2 - 24 in	C. HOT	SS	A
Cap-Welded	1/2 - 24 in	C. HOT	SS	A
Concentric Reducer-Seamless	1/2 - 24 in	C. HOT	SS	A
Concentric Reducer-Welded	1/2 - 24 in	C. HOT	SS	A
Cross-Welded	1/2 - 24 in	C. HOT	SS	A
Eccentric Reducer-Seamless	1/2 - 24 in	C. HOT	SS	A
Eccentric Reducer-Welded	1/2 - 24 in	C. HOT	SS	A
Equal Tee-Seamless	1/2 - 24 in	C. HOT	SS	A
Equal Tee-Welded	1/2 - 24 in	C. HOT	SS	A
Hex Head Thread plug	1/2 - 4 in	C. HOT	SS	A
Reducer Tee-Seamless	1/2 - 24 in	C. HOT	SS	A
Reducer Tee-Welded	1/2 - 24 in	C. HOT	SS	A
Round Head Thread Plug	1/2 - 4 in	C. HOT	SS	A
Slip on Flange	1/2 - 12 in	C. HOT	SS	A
Socket Olet	1/2 - 4 in	C. HOT	SS	A
Socket Weld 45	1/2 - 4 in	C. HOT	SS	A
Socket Weld 90	1/2 - 4 in	C. HOT	SS	A
Socket Weld Cap	1/2 - 4 in	C. HOT	SS	A
Socket Weld Coupling	1/2 - 4 in	C. HOT	SS	A
Socket Weld Cross	1/2 - 4 in	C. HOT	SS	A
Socket Weld Flange	1/2 - 12 in	C. HOT	SS	A
Socket Weld Half Coupling	1/2 - 4 in	C. HOT	SS	A
Socket Weld Tee	1/2 - 4 in	C. HOT	SS	A
Socket Weld Union	1/2 - 4 in	C. HOT	SS	A
Stub End-Seamless	1/2 - 24 in	C. HOT	SS	A
Stub End-Welded	1/2 - 24 in	C. HOT	SS	A
Threaded 45	1/2 - 4 in	C. HOT	SS	A
Threaded 90	1/2 - 4 in	C. HOT	SS	A

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



Threaded Cap	1/2 - 4 in	C. HOT	SS	A
Threaded Coupling	1/2 - 4 in	C. HOT	SS	A
Threaded Cross	1/2 - 4 in	C. HOT	SS	A
Threaded Flange	1/2 - 12 in	C. HOT	SS	A
Threaded Half Coupling	1/2 - 4 in	C. HOT	SS	A
Threaded Olet	1/2 - 4 in	C. HOT	SS	A
Threaded Street 90	1/2 - 4 in	C. HOT	SS	A
Threaded Tee	1/2 - 4 in	C. HOT	SS	A
Threaded Union	1/2 - 4 in	C. HOT	SS	A
Welded Olet	1/2 - 24 in	C. HOT	SS	A
Weldneck Flange	1/2 - 12 in	C. HOT	SS	A

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.